

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** ARGUS LIGHT s.r.o.

**Supplier's address:** ARGUS LIGHT s.r.o., Poličná 427 CZ 757 01 Valašské Meziříčí Czech republic

**Model identifier:** LED FLM-F E27 A60 7W NW

## Type of light source:

|   |     |                                 |      |
|---|-----|---------------------------------|------|
| Lighting technology used:                           | LED | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | E27 |                                 |      |
| Mains or non-mains:                                 | MLS | Connected light source (CLS):   | No   |
| Colour-tuneable light source:                       | No  | Envelope:                       | -    |
| High luminance light source:                        | No  |                                 |      |
| Anti-glare shield:                                  | No  | Dimmable:                       | No   |

## Product parameters

| Parameter  | Value                   | Parameter  | Value                  |
|--|-------------------------|--|------------------------|
| <b>General product parameters:</b>   |                         |  |                        |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer  | 7                       | Energy efficiency class  | E                      |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 850 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000                  |
| On-mode power ( $P_{on}$ ), expressed in W   | 7,0                     | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal   | 0,00                   |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal  | -                       | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 81                     |
| Outer dimensions without separate control gear, lighting control   | Height                  | Spectral power distribution in the range 250 nm to 800 nm, at full-load  | See image in last page |
|  | Width                   |  |                        |
|  | Depth                   |  |                        |

|   |      |                                       |                |  |
|---|------|---------------------------------------|----------------|--|
| parts and non-lighting control parts, if any (millimetre)   |      |                                       |                |  |
| Claim of equivalent power <sup>(a)</sup>  | -    | If yes, equivalent power (W)          | -              |  |
|   |      | Chromaticity coordinates (x and y)    | 0,381<br>0,378 |  |
| <b>Parameters for LED and OLED light sources:</b>   |      |                                       |                |  |
| R9 colour rendering index value   | 2    | Survival factor                       | 0,90           |  |
| the lumen maintenance factor  | 0,90 |                                       |                |  |
| <b>Parameters for LED and OLED mains light sources:</b>   |      |                                       |                |  |
| displacement factor (cos $\phi_1$ )   | 0,50 | Colour consistency in McAdam ellipses | 6              |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | -(b) | If yes then replacement claim (W)     | -              |  |
| Flicker metric (Pst LM)   | 0,8  | Stroboscopic effect metric (SVM)      | 0,3            |  |

(a) '-': not applicable;

(b) '-': not applicable;

